

High Abuse Surface Mount Fluorescent Linear

The LPN series is designed for general purpose lighting in high abuse environments.

Mounting

Surface mounts to ceilings or walls.

Lens

Vandal resistant, injection molded, UV stabilized, prismatic polycarbonate lens.

Housing

16 gauge cold rolled steel die formed to shape with seams welded and ground smooth.

Finish

Polyester powder coated after phosphate pretreatment for superior adhesion and corrosion resistance.

Hardware

Stainless steel, tamper-proof fasteners.

Wiring

All electrical components are mounted to the housing for wiring ease.


Certifications

VAR

UL listed damp location. For a wet location fixture of similar design, see our LPS series.

Variable, 120-277 V, 50/60Hz











I PNI		-		-		-	
LIIV							
	one	two	three	four	five	six	

		0110			
one	Lamps (not included)	three	Ballast	five	Finish
28	4 ft. 28 W T5	DM	Dimming	W	White
32	4 ft. 32 W T8 RS	EL	Electronic Instant Start, std T8		
4B	Two 2 ft. 40 W T5 RS Biax	PR	Program Rapid Start, std T5, option T8	six CU	Options Canadian UL Listing
two	Voltage	four	Fasteners Stainless steel allen head with pin	E1	One lamp emergency ballast Fuse and holder
120	120 V, 60 Hz	AP		FH	
277	277 V, 60 Hz	TP	Stainless steel torx head with pin		
347	347 V, 60 Hz	PH	Phillips, non-security		