



M100D

Marine Surface Mount Ceiling Fluorescent

PRODUCT SPECIFICATION

Overhead Lighting M100D Series

The M100D Series is designed and constructed for commercial marine and wet location surface mount ceiling applications. The design is drip-proof and easy to install and service.

Mounting

Surface-mounts to ceiling.

Housing

Die-formed marine grade aluminum housing with continuously welded seams and liquid tight cord grip.

Lens

Thermoformed white acrylic lens.

Lens Frame

Seamless extruded aluminum with piano hinge and spring loaded quarter-turn fasteners.

Lamp Holder

Vibration resistant spring loaded medium bi-pin lamp holders keep lamps securely in position.

Finish

White powder coat polyester finish with phosphate pretreatment to ensure superior adhesion.

Ballast

Standard universal 120-277 VAC, 50/60 Hz, electronic ballast.
**Contact factory for other options.*

Weight

2 ft: 15 lbs (6.8 Kg)

Certifications

IP 54 rated. USCG ABS approved.
UL 1598A marine listed.

Applications




- Narrow Housing
- Passageways
- Work Stations

Job Name _____

Fixture Type _____

Catalog No. _____

Approval _____ Date _____



one Luminaire Size

2 2-ft fixture

two Lamp Type

17 17W T8, (2 ft)
20 20W T12, (2 ft)

three Options

E1 One lamp emergency service
SJO 10' of 16/3 cable, prewired
2C Two circuit wired
DC 12-24 Volt DC

Modifications are available to meet custom requirements.
Specifications and dimensions are subject to change without notice.