



M3HL-LED

Hazardous Location and Marine **LED** Surface Mount Ceiling

PRODUCT SPECIFICATION

The M3(HL) is designed for use in marine, industrial and hazardous location environments.

Mounting

Surface mounts to ceilings via zinc-plated, corrosion and shock-resistant brackets.

Housing

16 gauge marine grade sheet aluminum die-formed to shape with cast aluminum ends.

Lens

Impact resistant, clear textured acrylic held in place with quick release spring brackets.

Finish

Polyester powder-coated after phosphate pretreatment for superior adhesion and corrosion resistance.

Driver

0-10Vdc, >0.9 PF, <20% THD
Factory programmable, Operating temp -40°C Min. to 50°C Max

Wiring

Reflector-mounted electrical components for easy wiring and maintenance accessed via quarter turn fasteners.

Weight

2 ft fixture - 14 lbs
4 ft fixture - 24 lbs

Certifications

UL 844 and UL 1598 marine listed. IP 65 rated.
Certified for
Class I Division 2, groups, A, B, C, and D,
Class II Division 2, groups F and G,
Class III.

Applications


- High moisture areas
- Oil platforms
- Processing plants
- Engine rooms

Job Name _____

Fixture Type _____

Catalog No. _____

Approval _____ Date _____



one two three four five
M3HL - - - **VAR** -

- | | | | |
|------------|--|--------------|----------------------------------|
| one | Luminaire Size | three | Color Temperature (white) |
| 2 | 2-ft fixture | 30 | 3000K |
| 4 | 4-ft fixture | 35 | 3500K |
| | | 40 | 4000K, standard |
| | | 50 | 5000K |
| two | LED Designation | four | Voltage |
| | Refer to the LED Source Table on Page 2 for available options. | VAR | Variable 120-277V, 50/60Hz |
| | | five | Options |
| | | EM | Emergency battery backup |

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.

CRI	LED Life
>80	>100,000

LED Source (Box 2)	3000K		3500K		4000K		5000K		Input Watts
	Delivered Lumens	L/W	Delivered Lumens	L/W	Delivered Lumens	L/W	Delivered Lumens	L/W	
2' Fixture									
1	3724	130	3781	132	3892	135	4003	139	28.7
2	7450	136	7561	138	7784	142	8006	146	54.8
3	11174	134	11342	136	11676	140	12009	144	83.5
4' Fixture									
1	7450	136	7561	138	7784	142	8006	146	54.8
2	14900	136	15122	138	15568	142	16012	146	109.6
3	22350	136	22683	138	23352	142	24018	146	164.4

Specified Output Option

LC Doane programmable drivers allows us to deliver a specific lumen output. If none of the options in the chart above fit your application, let us know the desired lumen output and we will do the rest. See the example below on how this will be specified:

Example Model:

M3HL4-XX¹40-VAR-(XX²/LUMENS)

LUMENS = You provide the lumens.

XX¹ = We will determine the number of rows.

XX² = We will provide the wattage information.

Photometric Data @ 80 CRI

90 CRI multiplier	.83
-------------------	-----

