



Overhead Lighting

607-LED Series

The 607-LED series is designed for general purpose naval lighting in maritime environments.

Mounting

Mounts flush within suspended ceilings.

Light Source

Four LED arrays, powered by 120V 60Hz drivers, provide 29.6W 0.26A of solid state illumination.

Lens

Optic Plus LED diffusing acrylic lens, standard.

Housing

Made from sheet aluminum die formed to shape with seams welded and ground smooth.

Finish


Polyester powder coated after phosphate pretreatment for superior adhesion and corrosion resistance.

Wiring

Supplied with 10' of LSTHOF-3 cable. 7XW-3 cable used with emergency circuit option (76).

Certifications

First Article Qualified.



MIL SPEC NUMBER	SLANT	SYMBOL	one
M16377	/	-	-

Slant	Electrical rating	Symbol	Mounting	one	Options
57	Four LED arrays	349SSL	Flush mount with diffusing acrylic lens	E	NEALS battery backup
76	Four LED arrays with NEALS battery backup	349EMSSL	349SSL with emergency battery backup	R 10G	Singled red LED array 10' LSFHOF-3 ground cable

Replacement Item	L.C. Doane Number	Military Number	NSN
1 Driver & 1 White Array Kit	B-3335A	-	-
Window & Gasket Assembly	B-1543L-SP	-	-
Shockmount	B-1591-BS	M16377/41-008	6210-01-393-4302
NEALS emergency battery pack	P-2860-S	-	-

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.