

# MIL-DTL-16377/58

## 606-LED Series

Detail Lighting LED



PRODUCT SPECIFICATION

# **Detail Lighting**

## 606-LED Series

21" dripproof 15 degree LED lighting fixture designed for installation above a mirror.

Surface mounted.

### **Light Source**

One full length LED array, powered by 120V 60Hz driver.

Optic Plus LED diffusing acrylic lens, standard

Supplied with 10 feet of 7XW-3 cable.

Overall Dimensions: 21" x 7" x 6"

### Certifications

First Article Qualified.



21" with duplex receptacle M16377/58-351.1SSL



21" with single receptacle and switch M16377/58-352SSL







Symbol Options

351.1SSL Duplex receptacle 352SSL Single receptacle with

DPST switch

**Options** one

Duplex receptacle Single receptacle with DPST switch

Replacement Item	L.C. Doane Number	Military Number	NSN	
1 Driver & 1 White Array Kit	B-3335A	-	-	
Window & Gasket Assembly	B-1625A-S	-	-	
Duplex Receptacle	P-1249	-	5935-00-283-4003	
Single Receptacle	P-1248-S	M2767/37-001-1	5935-00-086-8923	
DPST Toggle Switch	B-573-D	-	-	

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.