



MIL-DTL-16377/58

606 Series

Detail Lighting Fluorescent Lighting

PRODUCT SPECIFICATION

Detail Lighting 606 Series

21" dripproof 15 degree fluorescent lighting fixture designed for installation above a mirror.

Mounting

Surface mounted.

Light Source

Two 15W T12 lamps, powered by two 120V 60Hz ballasts.

Lens

Clear prismatic lens

Cable

Supplied with 10 feet of LSFHOF-3 cable.

Dimensions

Overall Dimensions: 21" x 7" x 6"

Net weight: 13 lbs.

Approximate shipping weight for package of four: 60 lbs.

Certifications

First Article Qualified.



21" with duplex receptacle
M16377/58-351.1
NSN 6210-01-044-5273



21" with single receptacle and switch
M16377/58-352
NSN 6210-00-115-9137



MIL-SPEC SLANT SYMBOL one

M16377 / 58 - -

Symbol Option

351.1 Duplex receptacle
352 Single receptacle with DPST switch

one

A Duplex receptacle
B Single receptacle with DPST switch

Option

Replacement Item	L.C. Doane Part Number	Symbol	NSN
Ballast	P-1739	M16377/44-001	6250-00-569-9502
Starter	P-119-S		6250-00-299-2884
15W T12 Lamp	P-1097-S		6240-00-583-3668
Prismatic Lens	B-1625-SP	M16377/58-002	6210-01-393-5130
DPST Toggle Switch	P-573-S	MS16569-1	5930-00-719-9659
Single Receptacle	P-1248-S	M2767/37-001-1	5935-00-086-8923
Duplex Receptacle	P-1249-S		5935-00-283-4003

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.