



Detail Lighting

609-LED Series

24" dripproof 15 degree LED lighting fixture designed for installation above a mirror.

Mounting

Surface mounted.

Light Source

One full length LED array, powered by 120V 60Hz driver.

Lens

Optic Plus LED diffusing acrylic lens, standard.

Cable

Supplied with 10 feet of 7XW-3 cable.

Dimensions

Overall Dimensions: 24" x 7" x 6".

Certifications

First Article Qualified.



24" with duplex receptacle
M16377/58 351SSL



24" with single receptacle and switch
M16377/58 352.1SSL



MIL-SPEC SLANT SYMBOL one
M16377 / **58** - -

Symbol	Option	one	Options
351SSL	Duplex receptacle	A	Duplex receptacle
352.1SSL	Single receptacle with DPST switch	B	Single receptacle with DPST switch

Replacement Item	L.C. Doane Part Number	Military Number	NSN
1 Driver & 1 White Array Kit	B-3335A	-	-
Window & Gasket Assembly	B-1614A-S	-	-
Duplex Receptacle	P-1249	-	5935-00-283-4003
Single Receptacle	P-1248-S	M2767/37-001-1	5935-00-086-8923
DPST Toggle Switch	B-573-D	-	-

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.