



Overhead Lighting

410-LED Series

The 410-LED Series is a watertight LED lighting fixture for general lighting.

Mounting

Mounts to ceiling surfaces or flush within them.

Light Source

One full length LED array, powered by 120V 60Hz driver.
Input Power: 3.9 Watts.

Lens

1/4 in. thick acrylic lens.

Housing

Constructed from marine grade aluminum. Polyester powder-coated after phosphate pre-treatment for superior adhesion and corrosion resistance.

Cable

Supplied with 10 feet of TXW-3 cable.

Standard Mounting

Overall Dimensions: 15-1/2" X 2-13/16" X 3-1/2"

Flush Mounting

Overall Dimensions: 17-3/4" X 5-1/4" X 3-1/2"

Certifications

First Article Qualified



Standard Mount, White Diffusing Lens
M16377/14-80.1



Flush Mount, Clear/White Lens
M16377/14-79.2



MIL-SPEC	SLANT	SYMBOL	one
M16377	14	-	-

Symbol	one	Symbol
79.1SSL Standard mount with clear/white directional lens	B	79.1SSL
79.2SSL Flush mount with clear/white directional lens	BF	79.2SSL
80.1SSL Standard mount with white diffusing lens	C	80.1SSL
80.2SSL Flush mount with white diffusing lens	CF	80.2SSL

Replacement Item	L.C. Doane Number	Symbol	NSN
LED Lamp	B-603-CS	-	-
LED Directional Lamp	B-603-BS	-	-
White Diffusing Lens	B-1473-NS	M16377/14-002	6210-00-647-2276
Prismatic Lens	B-770-ANS	M16377/14-001	6210-00-553-6793
Shockmount	B-1591-AS	M16377/41-010	6210-00-973-1748

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.