

# MIL-F-16377/14

410 Series

Overhead Lighting

Surface Mount

Flush Mount Fluorescent

PRODUCT SPECIFICATION

# Overhead Lighting 410 Series

The 410 Series is a watertight fluorescent lighting fixture for general lighting.

## Mounting

Mounts to ceiling surfaces or flush within them.

#### Light Source

One 8W T5 cool white lamp, powered by 120V 60Hz ballast.

#### Lens

1/4 in. thick white diffusing lens. Prismatic lens available.

#### Housing

Constructed from marine grade aluminum.

#### Cable

Supplied with 10 feet of LSDHOF-3 cable.

# Standard Mounting

Overall Dimensions: 15-1/2" X 2-13/16" X 3-1/2"

Net weight: 4 lbs. 3 oz. maximum.

Approximate shipping weight for package of ten: 50 lbs.

## Flush Mounting

Overall Dimensions: 17-3/4" X 5-1/4" X 3-1/2"

Net weight: 5 lbs. 2 oz. maximum.

Approximate shipping weight for package of ten: 65 lbs

# Certifications

First Article Qualified.



Standard Mount, White Diffusing Lens NSN: 6210-00-578-7703 M16377/14-79.1



Flush Mount, Clear/White Lens NSN: 6210-01-088-8990 M16377/14-80.2





M16377	/ 14	_	_	_	-
MIL-SPEC	SLANT	SYMBOL	one	two	three

Symbol	Mount	one	Mounting
, 79.1	Standard mount with	С	Standard mounting with clear lens
	clear/white directional lens	CF	Flush mounting with clear lens
79.2	Flush mount with	В	Standard mounting with difussing lens
	clear/white directional lens	BF	Flush mounting with diffusing lens
80.1	Standard mount with white diffusing lens	one	LED Color Array
80.2	Flush mount with white	R	Red
	diffusing lens	В	Blue
		Υ	Amber

	Switch Option One DPST switch

Replacement Item	L.C. Doane Part Number	Symbol	NSN	
Ballast	P-337-S	M16377/45-001	6250-00-295-2735	
8W T5 Lamp	P-1-S	MS15588-3	6240-00-299-5546	
White Diffusing Lens	B-1473-NS	M16377/14-002	210-00-647-2276	
Prismatic Lens	B-770-ANS	M16377/14-001	6210-00-553-6793	
Shockmount	B-1591-AS	M16377/41-010	6210-00-973-1748	

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.