



MIL-F-16377/49

21 Series

Explosion Watertight

PRODUCT SPECIFICATION

Portable Light 21 Series

A portable fluorescent extension light fixture. The housing is marine grade cast aluminum and 1/4" thick cast acrylic. Supplied with 50 feet of 16/3 cable which will accommodate a 150 lb. load. The fixture is capable of operating in an ambient temperature of 1350 °F and is suitable for Class 1, Group D, hazardous locations as defined by the National Electrical Code. 8W, 115 volts, 60Hz.

Overall Dimensions:

22-3/4" long X 3" diameter approximately.

Net Weight:

10 lbs. 0 oz. maximum.

Approximate shipping weight for package of six:

65 lbs

Certifications

First Article Qualified.



M16377/49-306.2
6230-00-244-3996



MIL-SPEC

SLANT

SYMBOL

M16377

49

306.2

Replacement Item	L.C. Doane Number	Military Number	NSN
Globe Assembly	B-1516-S	M16377/49-001	6230-00-451-6450
Hook Assembly	B-1518-S	M16377/49-002	-
Handle Assembly	B-1522-S	M16377/49-003	-
Bushing	P-1177-S	M16377/49-004	-

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.