



Overhead Lighting

472 Series

The 472 Series is a watertight fluorescent lighting fixture for general lighting. The housing is constructed from marine grade aluminum. Available with either a white diffusing or a clear and white prismatic 1/4" thick lens

Power
120 volts, 60 hertz.

Light Source
Two 15W T12 cool white lamps

Lens
Clear prismatic acrylic lens

Housing
Marine grade aluminum

Cable
supplied with 10 feet of 16/3 cable.

Standard Mount
Overall Dimensions: 23" X 7 5/8" X 3 7/8"
Net Weight: 8 lbs. 11oz. maximum
Approximate shipping weight for package of six: 61 lbs.

Flush Mount
Overall Dimensions: 25 5/16" X 9 1/16" X 3 3/8"
Net weight: 10 lbs. 1 oz. maximum
Approximate shipping weight for package of six: 70 lbs.

Certifications
First Article Qualified.



Standard Mount, White Diffusing Lens
NSN 6210-01-103-9867
M16377/65-81



Flush Mount, Clear/White Prismatic Lens
M16377/65-345,3
NSN 6210-01-283-8702



MIL SPEC NUMBER	SLANT	SYMBOL	one	two	three	four
M16377/65	65	-	-	-	-	-

Symbol	Mount	one	Filter option	three	Cable option
81	Standard mount white	Y	Amber	15G	15' lowsmoke ground cable
81.1	Flush mount white	B	Blue	20G	20' lowsmoke ground cable
345.2	Standard mount clear and white prismatic lens	T	Red		
345.3	Flush mount clear and white prismatic lens	G1.0	Grey 1.0%	four	Other option
		G2.0	Grey 2.5%	A1	Amendment 1, high efficiency ballast and low smoke cable
		two	Switch option		
		S	One switch		
		SS	Two switches		

Replacement Item	L.C. Doane Number	Military Number	NSN
White Diffusing Lens	B-1687-NS	M16377/65-001	-
Clear/ White Prismatic Lens	B-1688-NS	M16377/65-002	-
Shockmount	B-1591-BS	M16377/41-009	6210-00-973-1747
Ballast	-	M16377/44-001	6250-00-569-9502
Lampholders	-	M970/11-1	6250-00-284-0481
Starter	FS-2	W-S-755	6250-00-299-2884
Starter Socket	-	M970/13-1	6250-00-295-2738

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.